

Y
M E_u
N₀

й Specification For Electromagnetic Flowmeter

General	1	Instrument Name					
	2						
	3	Pipe Size	mm	/ ρ	O.D./I.D.	273/260	
	4	Pipe Mat'l	Pipe Class		20#		
	5	Fluid	:	Phase	°	r	
Process Condition	6	Oper. Temp.	Н	Design Temp.	Н		
	7	Oper. Press.	MPa	Design Press.	MPa	0.4	
	8	Flow Rate	γ β Unit		Max.Flow	Nor.Flow	Min.Flow
	9	Kg/h(r Liquid, Steam),Nm3/h(r Gas)	Kg/h		240000		
	10	Oper.Density	kg/m ³	1000			
	11		2/s	μ H	Dyn Visc	mPa.s	1
	12	Min. Conductivity (us/cm)					
	13						
	14						
	15						
Meter Unit	16						
	17						
	18						
	19						
	20	μ	Kin Visc mm				
	21						
	22	Environment Electromagnetism (A/m)				Ў 400A/m	
	23	μ	Field Vibration		g :	55HZ à	0.5mm
	24	“H J H	Max. Allow Press. Drop (MPa)			0.05	
	25	μ	Model				
Transmitter	26	λ	Cali. Principle	Accuracy	і ?	α 0.5%	
	27	Calibration Range		γ Available Range	0~300t/h		
	28	Allow Oper.Temp.		Н J H Pressure Rating	-40~80Н	PN16	
	29	Type	Mounting			№	
	30	“H μ	Output Signal	Ln q	d	H	Flange R
	31	Power Supply		’ Elec. Conn.	220VAC	1/2"NPT(F) 2	6
	32	Housing Mat'l		Local Indicator		LCD	
	33	Encl. Protec.		Explosion Proof		IP66	
	34	і	Mounting Tools	Mounting Bracket			
	Access.	35	Ў	Bolt and Nut	Ⓟ	Check Valve	
36		G	Surge Protection Device				
37		L	Manufacture				
38		γ μ	Requisition No.				
Note: Ѡ à β “ Â							
L ш ‘ 1. н F з ê 170046D-60-K-1/ 311 İ Â							

L

ρ ASEC й б 322 .